What is claimed is:

mechanism to pivot said orifice.

2

1	1.	An interface device for interfacing instruments to a simulation system to	
2	enable a user to interact with the simulation system to perform a medical procedure on a		
3	simulated anatomy of a virtual patient, said interface device comprising:		
4	a peripheral in the form of a mock medical instrument capable of selective		
5	manipulation by the user;		
6.	an orifice for receiving said instrument;		
7	a guide tube for directing said instrument from said orifice into said interface device;		
8	a capture mechanism for engaging said instrument to enable said interface device to		
9	measure manipulation of and provide force feedback to said instrument; and		
10	a sensing assembly to measure manipulation of and provide force feedback to said		
11	instrument, wherein said sensing assembly includes:		
12		motion detection means to measure manipulation of said captured instrument	
13	and provide signals indicating said measured manipulation to said simulation system		
14	to simulate said medical procedure; and		
15	• •	force application means to apply force feedback to said captured instrument in	
16	respo	nse to control signals from said simulation system.	
1	2.	The device of claim 1 wherein said instrument includes an endoscope.	
1	3.	The device of claim 1 wherein said instrument includes a nested instrument	
2	assembly, and said interface device further includes:		
3		a plurality of capture mechanisms each engaging a corresponding instrument	
4	of said instrument assembly to enable said interface device to measure manipulation		
5	of and provide force feedback to that instrument; and		
6		a plurality of sensing assemblies each measuring manipulation of and	
7	providing force feedback to said corresponding instrument.		
1	4.	The device of claim 1 wherein said interface device further includes a pivoting	

1	5. An interface device for interfacing instruments to a simulation system to		
2	enable a user to interact with the simulation system to perform a medical procedure on a		
3	simulated anatomy of a virtual patient, said interface device comprising:		
4	a plurality of peripherals in the form of mock medical instruments capable of selective		
5	manipulation by the user;		
6	a plurality of orifices for receiving said instruments;		
7	a plurality of guide tubes for directing said instruments from said orifices into said		
8	interface device;		
9	a plurality of capture mechanisms for engaging said instruments to enable said		
10	interface device to measure manipulation of and provide force feedback to said instruments;		
11	and		
12	a plurality of sensing assemblies to measure manipulation of and provide force		
13	feedback to said instruments, wherein each said sensing assembly includes:		
14	motion detection means to measure manipulation of a corresponding captured		
15	instrument and provide signals indicating said measured manipulation to said		
16	simulation system to simulate said medical procedure; and		
17	force application means to apply force feedback to said corresponding		
18	captured instrument in response to control signals from said simulation system.		

1

2

1

2

3

4

5

6

7

8

9

- 6. The device of claim 5 wherein at least one of said instruments includes a nested instrument assembly.
- In an interface device for interfacing instruments to a simulation system to 7. enable a user to interact with the simulation system to perform a medical procedure, a capture mechanism for engaging an instrument inserted within the interface device to enable the interface device to measure manipulation of and provide force feedback to that instrument, said capture mechanism comprising:

a grasping member for engaging said instrument to enable said interface device to measure manipulation of and provide force feedback to said instrument; and

an actuator for activating said grasping member to engage said instrument in response to user manipulation of said instrument.

1	8.	A method for interfacing instruments to a simulation system, via an interface			
2	device, to enable a user to interact with the simulation system to perform a medical procedure				
3	on a simulated anatomy of a virtual patient, said method comprising the steps of:				
4	(a) in	(a) inserting a peripheral in the form of a mock medical instrument into said interface			
5	device via an orifice and guide tube, and selectively manipulating said instrument within said				
6	interface device;				
7	(b) engaging said instrument, via a capture mechanism, to enable said interface				
8	device to measure manipulation of and provide force feedback to said instrument;				
9	(c) measuring manipulation of said captured instrument and providing signals				
10	indicating said measured manipulation to said simulation system to simulate said medical				
11	procedure; and				
12	(d) applying force feedback to said captured instrument in response to control signals				
13	from said simulation system.				
1	9.	The method of claim 8 wherein said instrument includes an endoscope.			
1	10.	The method of claim 8 wherein said instrument includes a nested instrument			
2	assembly, and step (b) further includes:				
3		(b.1) engaging each instrument of said instrument assembly to enable said			
4	interface device to measure manipulation of and provide force feedback to that				
5	instrument;				
6		step (c) further includes:			
7		(c.1) measuring manipulation of said each instrument and providing signals			
8	indicating said measured manipulation to said simulation system; and				
9		step (d) further includes:			
10		(d.1) applying force feedback to said each instrument in response to control			
11	signals from said simulation system.				
1	11	The method of claim & wherein sten (a) further includes:			

(a.1) pivoting said orifice to a desired orientation.